



Coaxial Termination



Part No: HD-040CL100NK1

1.0 Mechanical Specifications		
1.1	Connector type	N type Female
1.2	Body material	Aluminum
1.3	Finish	Anticorrosion black paint
1.4	Connector centre conductor	Gold-plated beryllium copper
1.5	Connector outer material	Brass with nickel alloy plating
1.6	Dimensions	153*76*76 mm
1.7	Weight	1.45 kg
1.8	Operation temp	-55°C - +125°C
2.0 Electrical Specifications		
2.1	Frequency Range	DC-4 GHz
2.2	VSWR (Max)	1.15
2.3	Power Handling	100 W (Avg), 5 kW (Peak) 5μs pulse width Power derates linearly against temp increase
2.4	Nominal Impedance	50 Ω
3.0 Outline Drawings		



Revision History

Date	Revision	Changes
24-Mar-2007	1	First release

Information furnished is believed to be accurate and reliable. However, HengDa Microwave assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of HengDa Microwave. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. HengDa Microwave products are not authorized for use as critical components in life support devices or systems without express written approval of HengDa Microwave.

© 2002 Xi'an HengDa Microwave Technology Development Company - All rights reserved

Email: market@hdmicrowave.com

www.hdmicrowave.com