



Coaxial Termination



Part No: HD-040CL1500NJ

1.0 Mechanical Specifications	
1.1	Connector type N Male
1.2	Connectors Brass Nickel Plated
1.3	Male Pin Brass Gold Plated
1.4	Female Pin Beryllium Copper Gold Plated
1.5	Housing Aluminum, Black Anodize
1.6	Dimensions 549x170x410 mm
1.7	Weight 32 kg
1.8	Operation temp -55°C ~ +125°C
2.0 Electrical Specifications	
2.1	Frequency Range DC-4 GHz
2.2	VSWR (Max) 1.70
2.3	Power rating Avg Power: 1500 W to 25°C ambient temperature, derated linearly to 150 W @ 125°C. Peak Power: 10 kW, 5µs pulse width with 15% duty cycle
2.4	Cooling method Forced draft
2.5	Nominal impedance 50 Ω
3.0 Outline Drawings	



Revision History

Date	Revision	Changes
24-Mar-2007	1	First release

Information furnished is believed to be accurate and reliable. However, HengDa Microwave assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of HengDa Microwave. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. HengDa Microwave products are not authorized for use as critical components in life support devices or systems without express written approval of HengDa Microwave.

© 2002 Xi'an HengDa Microwave Technology Development Company - All rights reserved

Email: market@hdmicrowave.com

www.hdmicrowave.com