



Crossguide Directional Coupler

Part No: HD-120W+C20PPPPC
 HD-120W+C30PPPPC
 HD-120W+C40PPPPC

1.0 Mechanical Specifications				
1.1	Waveguide Type	WR75		
1.2	Flange Type	FBP120 (Cover)		
1.3	Material	Copper/Brass		
1.4	Inside Finish	Silver plating		
1.5	Outside Finish	Anticorrosion black paint		
1.6	Temperature Range	-40°C ~ +70° C		
2.0 Electrical Specifications				
	Part No	HD-120W+C20PPPPC	HD-120W+C30PPPPC	HD-120W+C40PPPPC
2.1	Frequency range	10-15GHz		
2.2	Operating Bandwidth (%)	20% of waveguide bandwidth		
2.3	VSWR (Max)	1.1:1 (Main line); 1.15:1 (Secondary line)		
2.4	Coupling	20 ± 0.7dB	30 ± 1.0 dB	40 ± 1.5 dB
2.5	Frequency Sensitivity (Max)	± 1.0 dB	± 1.0 dB	± 1.0dB
2.6	Directivity (Min)	20 dB	20 dB	18 dB
3.0 Outline Drawings				



Revision History

Date	Revision	Changes
20-Oct-2004	1	First release

Information furnished is believed to be accurate and reliable. However, HengDa Microwave assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of HengDa Microwave. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. HengDa Microwave products are not authorized for use as critical components in life support devices or systems without express written approval of HengDa Microwave.

© 2002 Xi'an HengDa Microwave Technology Development Company - All rights reserved

Email: market@hdmicrowave.com

www.hdmicrowave.com